



# MAXPOWER


## CS6U-325|330|335|340P


Canadian Solar's modules use the latest innovative cell technology, increasing module power output and system reliability, ensured by 15 years of experience in module manufacturing, well-engineered module design, stringent BOM quality testing, an automated manufacturing process and 100% EL testing.


### KEY FEATURES

- 

Excellent module efficiency of up to 17.49%
- 

Outstanding low irradiance performance up to 96.5 %
- 

High PTC rating of up to 92.21 %
- 

IP68 junction box for long-term weather endurance
- 

Heavy snow load up to 5400 Pa, wind load up to 2400 Pa



linear power output warranty



product warranty on materials and workmanship

### MANAGEMENT SYSTEM CERTIFICATES\*

ISO 9001:2008 / Quality management system  
 ISO 14001:2004 / Standards for environmental management system  
 OHSAS 18001:2007 / International standards for occupational health & safety

### PRODUCT CERTIFICATES\*

IEC 61215 / IEC 61730: VDE / CE / CQC / MCS / INMETRO / CEC AU  
 UL 1703 / IEC 61215 performance: CEC listed (US) / FSEC (US Florida)  
 UL 1703: CSA / IEC 61701 ED2: VDE / IEC 62716: VDE  
 UNI 9177 Reaction to Fire: Class 1  
 IEC 60068-2-68: SGS  
 Take-e-way



\* As there are different certification requirements in different markets, please contact your local Canadian Solar sales representative for the specific certificates applicable to the products in the region in which the products are to be used.

**CANADIAN SOLAR (USA), INC.** is committed to providing high quality solar products, solar system solutions and services to customers around the world. As a leading PV project developer and manufacturer of solar modules with over 21 GW deployed around the world since 2001, Canadian Solar Inc. (NASDAQ: CSIQ) is one of the most bankable solar companies worldwide.


\*For detail information, please refer to Installation Manual.

### CANADIAN SOLAR (USA), INC.


3000 Oak Road, Suite 400, Walnut Creek, CA 94597, USA | [www.canadiansolar.com/na](http://www.canadiansolar.com/na) | [sales.us@canadiansolar.com](mailto:sales.us@canadiansolar.com)

## ENGINEERING DRAWING (mm)


### Rear View




### Frame Cross Section A-A



### Mounting Hole



## CS6U-320P / I-V CURVES



## ELECTRICAL DATA | STC\*

| CS6U                                      | 325P                                    | 330P   | 335P   | 340P   |
|---|---|--------|--------|--------|
| Nominal Max. Power (P <sub>max</sub> )    | 325 W                                   | 330 W  | 335 W  | 340 W  |
| Opt. Operating Voltage (V <sub>mp</sub> ) | 37.0 V                                  | 37.2 V | 37.4 V | 37.6 V |
| Opt. Operating Current (I <sub>mp</sub> ) | 8.78 A                                  | 8.88 A | 8.96 A | 9.05 A |
| Open Circuit Voltage (V <sub>oc</sub> )   | 45.5 V                                  | 45.6 V | 45.8 V | 45.9 V |
| Short Circuit Current (I <sub>sc</sub> )  | 9.34 A                                  | 9.45 A | 9.54 A | 9.62 A |
| Module Efficiency                         | 16.72%                                  | 16.97% | 17.23% | 17.49% |
| Operating Temperature                     | -40°C ~ +85°C                           |        |        |        |
| Max. System Voltage                       | 1000 V (IEC) or 1000 V (UL)             |        |        |        |
| Module Fire Performance                   | TYPE 1 (UL 1703) or CLASS C (IEC 61730) |        |        |        |
| Max. Series Fuse Rating                   | 15 A                                    |        |        |        |
| Application Classification                | Class A                                 |        |        |        |
| Power Tolerance                           | 0 ~ + 5 W                               |        |        |        |

\* Under Standard Test Conditions (STC) of irradiance of 1000 W/m<sup>2</sup>, spectrum AM 1.5 and cell temperature of 25°C.

## ELECTRICAL DATA | NMOT\*

| CS6U                                      | 325P   | 330P   | 335P   | 340P   |
|---|--------|--------|--------|--------|
| Nominal Max. Power (P <sub>max</sub> )    | 239 W  | 242 W  | 246 W  | 250 W  |
| Opt. Operating Voltage (V <sub>mp</sub> ) | 34.0 V | 34.2 V | 34.4 V | 34.6 V |
| Opt. Operating Current (I <sub>mp</sub> ) | 7.01 A | 7.08 A | 7.15 A | 7.22 A |
| Open Circuit Voltage (V <sub>oc</sub> )   | 42.4 V | 42.5 V | 42.6 V | 42.7 V |
| Short Circuit Current (I <sub>sc</sub> )  | 7.54 A | 7.63 A | 7.70 A | 7.77 A |

\* Under Nominal Module Operating Temperature (NMOT), irradiance of 800 W/m<sup>2</sup>, spectrum AM 1.5, ambient temperature 20°C, wind speed 1 m/s.

## PERFORMANCE AT LOW IRRADIANCE

Outstanding performance at low irradiance, with an average relative efficiency of 96.5 % from irradiances, between 200 W/m<sup>2</sup> and 1000 W/m<sup>2</sup> (AM 1.5, 25°C).

The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to on-going innovation, research and product enhancement, Canadian Solar Inc. reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

Caution: For professional use only. The installation and handling of PV modules requires professional skills and should only be performed by qualified professionals. Please read the safety and installation instructions before using the modules.

## MECHANICAL DATA

| Specification          | Data   |
|------------------------|--|
| Cell Type              | Poly-crystalline, 6 inch                                     |
| Cell Arrangement       | 72 (6 × 12)  |
| Dimensions             | 1960 × 992 × 40 mm<br>(78.7 × 39.1 × 1.57 in)                |
| Weight                 | 22.4 kg (49.4 lbs)   |
| Front Cover            | 3.2 mm tempered glass  |
| Frame                  | Anodized aluminium alloy                                     |
| J-Box                  | IP68, 3 diodes   |
| Cable                  | 4.0 mm <sup>2</sup> (IEC), 12 AWG (UL),<br>1160 mm (45.7 in) |
| Connector              | T4 series (IEC / UL)   |
| Per Pallet             | 26 pieces. 635 kg (1400 lbs)                                 |
| Per Container (40' HQ) | 624 pieces   |

## TEMPERATURE CHARACTERISTICS

| Specification                               | Data         |
|---|--------------|
| Temperature Coefficient (P <sub>max</sub> ) | -0.41 % / °C |
| Temperature Coefficient (V <sub>oc</sub> )  | -0.31 % / °C |
| Temperature Coefficient (I <sub>sc</sub> )  | 0.05 % / °C  |
| Nominal Module Operating Temperature        | 43 ± 2 °C    |

## PARTNER SECTION

