

S O L S T I C E™ AC Microinverter by [e] enphase® ENERGY

M215—MICROINVERTER



The Enphase Energy Microinverter System improves energy harvest, increases reliability, and dramatically simplifies design, installation and management of solar power systems.

The Enphase System includes the microinverter, the Envoy Communications Gateway, and Enlighten, Enphase's monitoring and analysis software.

PRODUCTIVE

- Maximum energy production
- Resilient to dust, debris and shading
- Performance monitoring per module

RELIABLE

- System availability greater than 99.8%
- No single point of system failure

SMART

- Quick and simple design, installation and management
- 24/7 monitoring and analysis

SAFE

- Low voltage DC
- Reduced fire risk

CertainTeed
SAINT-GOBAIN
Solar

M215 — MICROINVERTER TECHNICAL DATA

Input Data (DC)	M215-60-2LL-S22/S23 and M215-60-2LL-S22-NA/S23-NA (Ontario)	
Recommended input power (STC)	190 - 260W	
Maximum input DC voltage	45V	
Peak power tracking voltage	22V - 36V	
Operating range	16V - 36V	
Min./Max. start voltage	22V/45V	
Max. DC short circuit current	15A	
Max. input current	10.5A	
Output Data (AC)	@208 Vac	@240 Vac
Maximum output power	215W	215W
Nominal output current	1.0A (arms at nominal duration)	0.9A (arms at nominal duration)
Nominal voltage/range	208V/183-229V	240V/211-264V
Extended voltage/range	208V/179-232V	240V/206-269V
Nominal frequency/range	60.0/59.3-60.5 Hz	60.0/59.3-60.5 Hz
Extended frequency range	60.0/59.2-60.6 Hz	60.0/59.2-60.6 Hz
Power Factor	>0.95	>0.95
Maximum units per 20A branch circuit	25 (three phase)	17 (single phase)
Maximum output fault current	1.05 Arms, over 3 cycles; 25.2 Apeak, 1.74ms duration	
Efficiency		
CEC weighted efficiency	96.0%	
Peak inverter efficiency	96.3%	
Static MPPT efficiency (weighted, reference EN50530)	99.6%	
Dynamic MPPT efficiency (fast irradiation changes, reference EN50530)	99.3%	
Night time power consumption	46mW	
Mechanical Data		
Ambient temperature range	-40°C to + 65°C	
Operating temperature range (internal)	-40°C to + 85°C	
Dimensions (WxHxD)	17.3 cm x 16.4 cm x 2.5 cm (6.8" x 6.45" x 1.0")*	
Weight	1.6 kg (3.5 lbs)	
Cooling	Natural convection - No fans	
Enclosure environmental rating	Outdoor - NEMA 6	* without mounting bracket
Features		
Compatibility	Pairs with most 60-cell PV modules	
Communication	Power line	
Warranty	25-year limited warranty	
Monitoring	Free lifetime monitoring via Enlighten software	
Compliance	UL1741/IIEEE1547, FCC Part 15 Class B CAN/CSA-C22.2 NO. 0-M91, 0.4-04, and 107.1-01	



ASK ABOUT ALL OF OUR OTHER CERTAINTEED® PRODUCTS AND SYSTEMS:

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • FOUNDATIONS
GYPSUM • CEILINGS • INSULATION • PIPE

www.certainteed.com <http://blog.certainteed.com>

CertainTeed Corporation
P.O. Box 860
Valley Forge, PA 19482

Professional: 800-233-8990
Consumer: 800-782-8777

© 10/12 CertainTeed Corporation, Printed in the U.S.A.
Code No. 20-20-3394

