

LG370Q1C-V5 | LG365Q1C-V5




LG NeON® R is powerful solar module that provides world-class performance. A new cell structure that eliminates electrodes on the front maximizes the utilization of light and enhances reliability. LG NeON® R is a result of LG's efforts to increase customer's values beyond efficiency. LG NeON® R features enhanced durability, performance under real -world conditions, an enhanced warranty and aesthetic design suitable for roofs.











Features



Aesthetic Roof

LG NeON® R has been designed with aesthetics in mind: the lack of any electrodes on the front creates an improved, modern aesthetic.



Extended Product Warranty

LG has extended the product warranty of the LG NeON $^{\odot}$ R to 25 years which is top level of the industry.



Better Performance on a Sunny Day


LG NeON® R now performs better on sunny days, thanks to its improved temperature coefficient.



More generation per square meter

The LG NeON® R has been designed to significantly enhance its output, making it efficient even in limited space.

About LG Electronics







LG370Q1C-V5 | LG365Q1C-V5

General Data

Cell Properties(Material / Type)	Monocrystalline / N-type
Cell Maker	LG
Cell Configuration	60 Cells (6 x 10)
Module Dimensions(L x W x H)	1,700mm x 1,016mm x 40mm
Weight	17.5 kg
Glass(Thickness / Material)	2.8mm / Tempered Glass with AR Coating
Backsheet(Color)	White
Frame(Material)	Anodized Aluminium
Junction Box(Protection Degree)	IP68 with 3 Bypass Diodes
Cables(Length)	1,000mm x 2EA
Connector(Type / Maker)	MC4 / MC

Certifications and Warranty

IEC 61215-1/-1-1/2:2016, IEC 61730-1/2:2016 UL 1703 ISO 9001, ISO 14001, ISO 50001 OHSAS 18001, PV CYCLE Salt Mist Corrosion Test IEC 61701:2012 Severity 6 Ammonia Corrosion Test IEC 62716:2013 Module Fire Performance Type 1 Fire Rating Class C (UL 790)	Certifications and Warranty				
Solutions	Certifications	IEC 61215-1/-1-1/2:2016, IEC 61730-1/2:2016			
ISO 9001, ISO 14001, ISO 50001		UL 1703			
Salt Mist Corrosion Test IEC 61701:2012 Severity 6 Ammonia Corrosion Test IEC 62716:2013 Module Fire Performance Type 1 Fire Rating Class C (UL 790)		ISO 9001, ISO 14001, ISO 50001			
Ammonia Corrosion Test IEC 62716:2013 Module Fire Performance Type 1 Fire Rating Class C (UL 790)		OHSAS 18001, PV CYCLE			
Module Fire Performance Type 1 Fire Rating Class C (UL 790)	Salt Mist Corrosion Test	IEC 61701:2012 Severity 6			
Fire Rating Class C (UL 790)	Ammonia Corrosion Test	IEC 62716:2013			
	Module Fire Performance	Type 1			
	Fire Rating	Class C (UL 790)			
Product Warranty 25 Years	Product Warranty	ty 25 Years			
Output Warranty of Pmax Linear Warranty*	Output Warranty of Pmax	Linear Warranty*			

^{* 1)} First year: 98% 2) After 1st year: 0.3% annual degradation 3) 25 years: 90.8%

Temperature Characteristics


remperature enaracteristics			
	NMOT*	[°C]	44 ± 3
	Pmax	[%/°C]	-0.30
	Voc	[%/°C]	-0.24
	Isc	[%/°C]	0.037

^{*} NMOT(Nominal Module Operating Temperature) : Irradiance 800 W/m², Ambient temperature 20 °C, Wind speed 1 m/s, Spectrum AM 1.5

Electrical Properties (NMOT)

Model		LG370Q1C-V5	LG365Q1C-V5	
Maximum Power (Pmax)	[W]	279	275	
MPP Voltage (Vmpp)	[V]	36.9	36.6	
MPP Current (Impp)	[A]	7.55	7.51	
Open Circuit Voltage (Voc)	[V]	40.3	40.2	
Short Circuit Current (Isc)	[A]	8.71	8.70	

I-V Curves



Electrical Properties (STC*)

Model		LG370Q1C-V5	LG365Q1C-V5
Maximum Power (Pmax)	[W]	370	365
MPP Voltage (Vmpp)	[V]	37.0	36.7
MPP Current (Impp)	[A]	10.01	9.95
Open Circuit Voltage (Voc, ±5%)	[V]	42.8	42.8
Short Circuit Current (Isc, ±5%)	[A]	10.82	10.80
Module Efficiency	[%]	21.4	21.1
Power Tolerance	[%]	0~+3	

^{*} STC (Standard Test Condition): Irradiance 1000 W/m², Cell Temperature 25 °C, AM 1.5

Operating Conditions


operating conditions				
Operating Temperature	[°C]	-40 ~ +90		
Maximum System Voltage	[V]	1,000		
Maximum Series Fuse Rating	[A]	20		
Mechanical Test Load(Front)	[Pa / psf]	5,400 / 113		
Mechanical Test Load(Rear)	[Pa / psf]	4,000 / 83.5		

^{*} Test Load = Design x Safety Factor(1.5)

Packaging Configuration

Number of Modules Per Pallet	[EA]	25
Number of Modules Per 40ft HQ Container	[EA]	650
Packaging Box Dimensions (L x W x H)	[mm]	1,750 x 1,120 x 1,221
Packaging Box Gross Weight	[kg]	473

Dimensions (mm / inch)







LG Electronics Inc.

Solar Business Division

2000 Millbrook Drive

Lincolnshire, IL 60069